

## ABSORB M

The Absorb M crash cushion barrier can be deployed safely in narrow working spaces, without compromising safety.

### PRODUCT OVERVIEW

The Absorb M crash cushion barrier can be deployed safely in narrow working spaces, without compromising safety. The uniquely designed crash cushion is only 67cm wide making the water filled barrier a suitable choice for narrow areas where road and interchangeable, workspaces are limited.

The ABSORB-M crash cushion system is the contractor's choice for a work zone ready MASH TL-2 or TL-3 tested crash cushion.



## ABSORB M

Featuring quick installation with no ground anchoring, easy deployment/removal, and the shortest length in its class. The crash cushion system utilizes nested elements to reduce inventory costs and a universal transition takes time and complexity out of installation.

RPM hire have a team of experienced and trained equipment experts, we can hire, safely install and deliver crash cushions and a range of traffic management equipment straight to your worksite.



## KEY FEATURES & BENEFITS

- Restricted to use in speed zones up to and including 80 km/h
- Rapid deployment and retrieval
- Universal transition
- Narrow footprint
- Can be deployed on almost any road surface
- Shortest MASH TL-2 & TL-3 Tested non-redirective
- Anchorless crash cushion, No ground anchoring required
- Durable long-life parts
- Approved for use in work zone locations
- Restricted to use in speed zones up to and including 60 km/h for TL-2 model (2-Element)
- Restricted to use in speed zones up to and including 80 km/h for TL-3 model (3-Element)

## SPECIFICATIONS

Classification	MASH TL-12	MASH TL-13
Length	446 cm	639 cm
Width	67 cm	67 cm
Height	110 cm	110 cm
Element Weight Empty	81 kg	81 kg
Element Weight Full	1030 kg	1030 kg

For more information and hire pricing for Short and Long term hire, contact RPM Hire on 1300 479 570 or email [enquiries@rpmhire.com.au](mailto:enquiries@rpmhire.com.au)